EASY COMBO EMERGENCY / EXIT LIGHT















Teknoware Easy Combo is a combination light, which can be used as either an emergency or emergency exit light. When fitted with the rotatable sign, Combo can show the direction arrow pointing up, down, left or right. When Combo is used as an emergency light, the sign is not installed.

Easy Combo can easily be surface or semi-flush mounted thanks to its practical design. Easy's wide product family offers an ideal choice when you want a single fixture for your entire property's needs.

5-year warranty

fitted with a rotatable sign, Combo can show the direction arrow pointing up, down, left or right available as a centrally supplied and self-contained light

viewing distance: 25 metres

protection rating: IP40 (or IP54 with an additional seal (sold separately)).

standard installation: surface and semi-flush mounted, ceiling and flag installation with a

separate mounting bracket

self-contained lights use a LiFePO₄ battery

OTHER ACCESSORIES FOR EMERGENCY LIGHTS

| Product Code | Product Name | Compatible Product Groups |
|--------------|--------------------------------|---|
| TWTB110 | Easy Combo IP54 gasket TWTB110 | Other Accessories for Emergency Exit Lights |

SELF-CONTAINED EMERGENCY EXIT LIGHTS WITH BATTERY AND

We reserve the rights to make modifications without notice.

Copyright © 2024 Teknoware. All rights reserved.

Date: May 24, 2024 | Source:

www.teknoware.com/en/emergency-lighting/emergency-exit-lights/emergency-exit-light-pr
oduct-families/easy-combo-emergency-exit-light



SELF-TESTING

| Product Code | Nominal Supply Voltage | Pictogram | Pictogram Info | Backup (h) |
|--------------|------------------------|-----------|----------------|------------|
| TWTB152WM | 220-240 V, 50/60 Hz AC | | 1-sided, 25 m | 1 |
| TWTB153WM | 220-240 V, 50/60 Hz AC | | 1-sided, 25 m | 3 |
| YB152WM120 | 220-240 V, 50/60 Hz AC | | 1-sided, 25 m | 1 |
| YB153WM120 | 220-240 V, 50/60 Hz AC | | 1-sided, 25 m | 3 |

SELF-CONTAINED EMERGENCY EXIT LIGHTS WITH BATTERY AND WIRELESS CENTRAL MONITORING

| Product Code | Nominal Supply Voltage | Pictogram | Pictogram Info | Backup (h) |
|--------------|------------------------|-----------|----------------|------------|
| TWTB152WA | 220-240 V, 50/60 Hz AC | | 1-sided, 25 m | 1 |
| TWTB153WA | 220-240 V, 50/60 Hz AC | | 1-sided, 25 m | 3 |
| YB152WA120 | 220-240 V, 50/60 Hz AC | | 1-sided, 25 m | 1 |
| YB153WA120 | 220-240 V, 50/60 Hz AC | | 1-sided, 25 m | 3 |

ADDRESSABLE 230 V CENTRALLY SUPPLIED EMERGENCY EXIT LIGHTS

| Product Code | Nominal Supply Voltage | Pictogram | Pictogram Info |
|--------------|----------------------------|-----------|----------------|
| TWTB151WK | 220-240 V, 50/60 Hz AC, DC | | 1-sided, 25 m |
| YB151WK120 | 220-240 V, 50/60 Hz AC, DC | | 1-sided, 25 m |

NON-ADDRESSABLE 230 V CENTRALLY SUPPLIED EMERGENCY EXIT LIGHTS

| Product Code | Nominal Supply Voltage | Pictogram | Pictogram Info |
|--------------|---------------------------|-----------|----------------|
| TWTB171W | 24-230 V, 50/60 Hz AC, DC | | 1-sided, 25 m |
| YB171W120 | 24-230 V, 50/60 Hz AC, DC | | 1-sided, 25 m |

PICTOGRAMS FOR EMERGENCY EXIT LIGHTS

| Product Code | Pictogram | Viewing Distance (m) | Compatible Product Groups |
|--------------|-----------|----------------------|---------------------------|
| PBB100 | | 25 | |

OPTIONAL MOUNTING ACCESSORIES FOR EMERGENCY EXIT LIGHTS



| Product Code | Product Name | Compatible Product Groups |
|--------------|--|--|
| TWTB101 | Easy Combo recess mounting frame TWTB101 | Easy: Combo Emergency / Exit Light, Easy Combo Emergency / Exit Light |
| TWTB103 | Easy Combo flag bracket TWTB103 | Easy: Combo Emergency / Exit Light, Easy Combo Emergency / Exit Light |
| TWTB104 | Easy Combo ceiling bracket TWTB104 | Easy: Combo Emergency / Exit Light, Easy Combo Emergency / Exit Light |
| TWTB105 | Easy Combo suspension bracket TWTB105 | Easy: Combo Emergency / Exit Light, Easy Combo Emergency / Exit Light |

