


# PLUS EMERGENCY EXIT LIGHT



Teknoware Plus is a durable emergency exit light for large spaces. The exit light with a metal body is particularly well suited for demanding conditions, such as parking and industrial halls, where the exit sign must be visible at distances of up to 60 metres. The product is dust- and waterproof (IP55) and durable against hard mechanic wear.

Plus can be used as one or two-sided, and the pictograms are easy to replace. Plus can be mounted to ceiling as standard, but it can be wall mounted with a separate bracket. The standard colour is white (RAL 9003), other RAL colours are available upon special order.

For demanding conditions: suitable for outdoor use and, in particular, industrial and parking halls

Metal body

Available as a centrally supplied and self-contained light

Dust- and waterproof

Viewing distance 60 metres

Can be used as one or two sided

Suitable for wall and ceiling installation

We reserve the rights to make modifications without notice.

Copyright © 2024 Teknoware. All rights reserved.

Date: May 22, 2024 | Source:

[www.teknoware.com/en/our-solutions/emergency-lighting-buildings/emergency-exit-lights/emergency-exit-light-product-families/plus-emergency-exit-light](http://www.teknoware.com/en/our-solutions/emergency-lighting-buildings/emergency-exit-lights/emergency-exit-light-product-families/plus-emergency-exit-light)



Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland  
Tel +358 3 883 020 | VAT-number FI01494751 | [teknoware.com](http://teknoware.com) | [emexit@teknoware.com](mailto:emexit@teknoware.com)

# SELF-CONTAINED ESCAP EMERGENCY EXIT LIGHTS WITH SUPER CAPACITOR AND SELF-TESTING

We reserve the rights to make modifications without notice.

Copyright © 2024 Teknoware. All rights reserved.

Date: May 22, 2024 | Source:

[www.teknoware.com/en/our-solutions/emergency-lighting-buildings/emergency-exit-lights/emergency-exit-light-product-families/plus-emergency-exit-light](http://www.teknoware.com/en/our-solutions/emergency-lighting-buildings/emergency-exit-lights/emergency-exit-light-product-families/plus-emergency-exit-light)



Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland  
Tel +358 3 883 020 | VAT-number FI01494751 | [teknoware.com](http://teknoware.com) | [emexit@teknoware.com](mailto:emexit@teknoware.com)

Product Code	Nominal Supply Voltage	Pictogram	Pictogram Info	Backup (h)
TWSF192WM	220-240 V, 50/60 Hz AC		2-sided, 60 m	1

## SELF-CONTAINED ESCAP EMERGENCY EXIT LIGHTS WITH SUPER CAPACITOR AND WIRELESS CENTRAL MONITORING

Product Code	Nominal Supply Voltage	Pictogram	Pictogram Info	Backup (h)
TWSF192WA	220-240 V, 50/60 Hz AC		2-sided, 60 m	1

## SELF-CONTAINED EMERGENCY EXIT LIGHTS WITH BATTERY AND SELF-TESTING

Product Code	Nominal Supply Voltage	Pictogram	Pictogram Info	Backup (h)
TWTF153WM	220-240 V, 50/60 Hz AC		2-sided, 60 m	3

## SELF-CONTAINED EMERGENCY EXIT LIGHTS WITH BATTERY AND WIRELESS CENTRAL MONITORING

Product Code	Nominal Supply Voltage	Pictogram	Pictogram Info	Backup (h)
TWTF153WA	220-240 V, 50/60 Hz AC		2-sided, 60 m	3

## ADDRESSABLE 230 V CENTRALLY SUPPLIED EMERGENCY EXIT LIGHTS

Product Code	Nominal Supply Voltage	Pictogram	Pictogram Info
TWTF151WK	220-240 V, 50/60 Hz AC, DC		2-sided, 60 m

## NON-ADDRESSABLE 230 V CENTRALLY SUPPLIED EMERGENCY EXIT LIGHTS

Product Code	Nominal Supply Voltage	Pictogram	Pictogram Info
TWTF171W	24-230 V, 50/60 Hz AC, DC		2-sided, 60 m

## ADDRESSABLE 24 V CENTRALLY SUPPLIED EMERGENCY EXIT LIGHTS

Product Code	Nominal Supply Voltage	Feature
TWTF141WK	24 V, 50/60 Hz AC, DC	Tapsa Control

We reserve the rights to make modifications without notice.

Copyright © 2024 Teknoware. All rights reserved.

Date: May 22, 2024 | Source:

[www.teknoware.com/en/our-solutions/emergency-lighting-buildings/emergency-exit-lights/emergency-exit-light-product-families/plus-emergency-exit-light](http://www.teknoware.com/en/our-solutions/emergency-lighting-buildings/emergency-exit-lights/emergency-exit-light-product-families/plus-emergency-exit-light)



Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland

Tel +358 3 883 020 | VAT-number FI01494751 | [teknoware.com](http://teknoware.com) | [emexit@teknoware.com](mailto:emexit@teknoware.com)