
ESC 80X ADAPTIVE EMERGENCY EXIT LIGHT TWT8051WKXT



Adaptive addressable 230 V centrally supplied emergency exit light

The Teknoware ESC 80X adaptive emergency exit light adapts automatically, if necessary, to warn about dangerous escape routes. Under normal conditions, the ESC 80X works like any normal exit light.

The ESC 80X is part of the versatile ESC 80 product family. Thanks to its high-quality electronics and powerful LEDs, the luminaire's pictogram is clear and even in all conditions. With its slender light-plate, this luminaire is particularly suitable for elegant spaces and, thanks to its IP44 enclosure class, also for humid spaces. The ESC 80X is currently available for central battery systems.

The single-sided ESC 80X comes with ceiling and wall mountings as standard. Installation is particularly easy and fast thanks to the separate mounting piece, to which the power supply is also connected. The luminaire can also be recess mounted using a separate recess frame – other mounting options with accessories are available, depending on the model. The ESC 80X comes with a five-year product warranty. The standard colour of the luminaire is white (RAL 9003), other RAL colours available on request.

We reserve the rights to make modifications without notice. Copyright © 2024 Teknoware. All rights reserved. Date: May 02, 2024 | Source: teknoware.com/en/our-solutions/emergency-lightingbuildings/esc-80x-adaptive-emergency-exit-light-twt8051wkxt



Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland Tel +358 3 883 020 | VAT-number FI01494751 | teknoware.com | emexit@teknoware.com

Product Code	TWT8051WKXT	
Feature	Tapsa Control	
Mounting (standard)	wall, ceiling	
Mounting (optional)	recess, flag, pendel	
Customs Code	94056080	
GTIN Code	06438045028552	
ETIM Product Class	EC001957	
Length	268 mm	
Width	40 mm	
Height	185 mm	
Weight	0,69 kg	
Max Input Power VA	6,6 VA	
Max Input Power W	4,2 W	
Nominal Supply Voltage	220-240 V, 50/60 Hz AC,DC	
Protection Class	II	
IP Class	IP44	
Temperature Range Min - Max	-30+50 °C	
Glow Wire Test of Plastic Materials	650 °C	
Viewing Distance	26 m	
Light Source	LED	
Body Material	plastic	
Aperture for Recess Mounting	45 x 275 mm	
Colour	RAL9005	
Electrical Installation	2/3 x 2,5 mm²	

ONE OR MORE OF THESE IS ALSO REQUIRED:

PICTOGRAMS FOR EMERGENCY EXIT



We reserve the rights to make modifications without notice. Copyright © 2024 Teknoware. All rights reserved. Date: May 02, 2024 | Source: teknoware.com/en/our-solutions/emergency-lightingbuildings/esc-80x-adaptive-emergency-exit-light-twt8051wkxt



Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland Tel +358 3 883 020 | VAT-number FI01494751 | teknoware.com | emexit@teknoware.com



Product Code	0	Viewing Distance (m)	Compatible Product Groups
PBV80261E1X	<u></u> <u> </u> →	26	
PBV80261E2X	€ 🔁	26	
PBV80262E3X	5 V	26	

OPTIONAL ACCESSORIES:

SHOCK PROTECTING COVERS FOR EMERGENCY LIGHTS



Product Code	Product Name	Compatible Product Groups
TW77507B	Shock protecting cover TW77507B	ESC 10 Emergency Exit Lights, ESC 80 Emergency Exit Lights

COMPATIBLE PRODUCTS:

OTHER EXTERNAL MODULES FOR CENTRAL BATTERY SYSTEMS



 Product Code
 Product Name

 TST6901
 Route Controller control unit TST6901

We reserve the rights to make modifications without notice. Copyright © 2024 Teknoware. All rights reserved. Date: May 02, 2024 | Source: teknoware.com/en/our-solutions/emergency-lightingbuildings/esc-80x-adaptive-emergency-exit-light-twt8051wkxt



Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland Tel +358 3 883 020 | VAT-number FI01494751 | teknoware.com | emexit@teknoware.com