


EASY: COMBO EMERGENCY / EXIT LIGHT



Teknoware Easy Combo is a combination light, which can be used as either an emergency or emergency exit light. When fitted with the rotatable sign, Combo can show the direction arrow pointing up, down, left or right. When Combo is used as an emergency light, the sign is not installed.

Easy Combo can easily be surface or semi-flush mounted thanks to its practical design. Easy's wide product family offers an ideal choice when you want a single fixture for your entire property's needs.

- 5-year warranty
 - fitted with a rotatable sign, Combo can show the direction arrow pointing up, down, left or right available as a centrally supplied and self-contained light
 - viewing distance: 25 metres
 - protection rating: IP40 (or IP54 with an additional seal (sold separately)).
 - standard installation: surface and semi-flush mounted, ceiling and flag installation with a separate mounting bracket
 - self-contained lights use a LiFePO₄ battery
- OTHER ACCESSORIES FOR EMERGENCY LIGHTS

Product Code	Product Name	Compatible Product Groups
TWTB110	Easy Combo IP54 gasket TWTB110	Other Accessories for Emergency Exit Lights

SELF-CONTAINED EMERGENCY EXIT LIGHTS WITH BATTERY AND

SELF-TESTING

Product Code	Nominal Supply Voltage	Pictogram	Pictogram Info	Backup (h)
TWTB152WM	220-240 V, 50/60 Hz AC		1-sided, 25 m	1
TWTB153WM	220-240 V, 50/60 Hz AC		1-sided, 25 m	3
YB152WM120	220-240 V, 50/60 Hz AC		1-sided, 25 m	1
YB153WM120	220-240 V, 50/60 Hz AC		1-sided, 25 m	3

SELF-CONTAINED EMERGENCY EXIT LIGHTS WITH BATTERY AND WIRELESS CENTRAL MONITORING

Product Code	Nominal Supply Voltage	Pictogram	Pictogram Info	Backup (h)
TWTB152WA	220-240 V, 50/60 Hz AC		1-sided, 25 m	1
TWTB153WA	220-240 V, 50/60 Hz AC		1-sided, 25 m	3
YB152WA120	220-240 V, 50/60 Hz AC		1-sided, 25 m	1
YB153WA120	220-240 V, 50/60 Hz AC		1-sided, 25 m	3

ADDRESSABLE 230 V CENTRALLY SUPPLIED EMERGENCY EXIT LIGHTS

Product Code	Nominal Supply Voltage	Pictogram	Pictogram Info
TWTB151WK	220-240 V, 50/60 Hz AC, DC		1-sided, 25 m
YB151WK120	220-240 V, 50/60 Hz AC, DC		1-sided, 25 m

NON-ADDRESSABLE 230 V CENTRALLY SUPPLIED EMERGENCY EXIT LIGHTS

Product Code	Nominal Supply Voltage	Pictogram	Pictogram Info
TWTB171W	24-230 V, 50/60 Hz AC, DC		1-sided, 25 m
YB171W120	24-230 V, 50/60 Hz AC, DC		1-sided, 25 m

OPTIONAL MOUNTING ACCESSORIES FOR EMERGENCY EXIT LIGHTS

Product Code	Product Name	Compatible Product Groups
TWTB101	Easy Combo recess mounting frame TWTB101	Easy: Combo Emergency / Exit Light, Easy Combo Emergency / Exit Light
TWTB103	Easy Combo flag bracket TWTB103	Easy: Combo Emergency / Exit Light, Easy Combo Emergency / Exit Light
TWTB104	Easy Combo ceiling bracket TWTB104	Easy: Combo Emergency / Exit Light, Easy Combo Emergency / Exit Light

We reserve the rights to make modifications without notice.
Copyright © 2024 Teknoware. All rights reserved.
Date: April 19, 2024 | Source: teknoware.com/en/emergency-lighting/emergency-lights/emergency-light-product-families/easy-combo-emergency-exit-light

Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland
Tel +358 3 883 020 | VAT-number FI01494751 | teknoware.com | emexit@teknoware.com



Product Code	Product Name	Compatible Product Groups
TWTB105	Easy Combo suspension bracket TWTB105	Easy: Combo Emergency / Exit Light, Easy Combo Emergency / Exit Light