

STEEL EMERGENCY EXIT LIGHT



Teknoware Steel is an elegant emergency exit light for high-class premises. The light plate in the elegant luminaire has a narrow, glossy metal frame. The luminaire can be used as one or two sided, and depending on the model, it is suitable for ceiling, wall, suspension or flag mounting. The centrally supplied lights and self-contained models with battery have an extended five-year product warranty, and the Escap models have an extended ten-year product warranty.

For high-class premises

Metal body

Available as a centrally supplied and self-contained light

The centrally supplied lights and self-contained models with battery have an extended five-year product warranty, and the Escap models have an extended ten-year product warranty.

Viewing distance 26, 40 or 60 m, depending on the model

Can be used as one or two sided

Suitable for ceiling, wall, suspension or flag installation

SELF-CONTAINED ESCAP EMERGENCY EXIT LIGHTS WITH SUPER
CAPACITOR AND SELF-TESTING

We reserve the rights to make modifications without notice.

Copyright © 2024 Teknoware. All rights reserved.

Date: July 16, 2024 | Source: teknoware.com/en/our-solutions/emergency-lighting-buildings/emergency-exit-lights/emergency-exit-light-product-families/steel-emergency-exit-light



Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland
Tel +358 3 883 020 | VAT-number FI01494751 | teknoware.com | emexit@teknoware.com

Product Code	Nominal Supply Voltage	Pictogram	Pictogram Info	Backup (h)
TWSE192WM	220-240 V, 50/60 Hz AC		2-sided, 26 m	1
TWSE292WM	220-240 V, 50/60 Hz AC		1-sided, 26 m	1
TWSE392WM	220-240 V, 50/60 Hz AC		2-sided, 26 m	1
TWSE492WM	220-240 V, 50/60 Hz AC		2-sided, 40 m	1
TWSE592WM	220-240 V, 50/60 Hz AC		2-sided, 40 m	1
TWSE692WM	220-240 V, 50/60 Hz AC		2-sided, 60 m	1
TWSE792WM	220-240 V, 50/60 Hz AC		2-sided, 60 m	1

SELF-CONTAINED ESCAP EMERGENCY EXIT LIGHTS WITH SUPER CAPACITOR AND WIRELESS CENTRAL MONITORING

Product Code	Nominal Supply Voltage	Pictogram	Pictogram Info	Backup (h)
TWSE192WA	220-240 V, 50/60 Hz AC		2-sided, 26 m	1
TWSE292WA	220-240 V, 50/60 Hz AC		1-sided, 26 m	1
TWSE392WA	220-240 V, 50/60 Hz AC		2-sided, 26 m	1
TWSE492WA	220-240 V, 50/60 Hz AC		2-sided, 40 m	1
TWSE592WA	220-240 V, 50/60 Hz AC		2-sided, 40 m	1
TWSE692WA	220-240 V, 50/60 Hz AC		2-sided, 60 m	1
TWSE792WA	220-240 V, 50/60 Hz AC		2-sided, 60 m	1

ADDRESSABLE 230 V CENTRALLY SUPPLIED EMERGENCY EXIT LIGHTS

Product Code	Nominal Supply Voltage	Pictogram	Pictogram Info
TWTE1151WK	220-240 V, 50/60 Hz AC, DC		2-sided, 30 m
TWTE1251WK	220-240 V, 50/60 Hz AC, DC		2-sided, 30 m
TWTE1351WK	220-240 V, 50/60 Hz AC, DC		2-sided, 30 m
TWTE151WK	220-240 V, 50/60 Hz AC, DC		2-sided, 26 m
TWTE251WK	220-240 V, 50/60 Hz AC, DC		1-sided, 26 m
TWTE351WK	220-240 V, 50/60 Hz AC, DC		2-sided, 26 m
TWTE451WK	220-240 V, 50/60 Hz AC, DC		2-sided, 40 m
TWTE551WK	220-240 V, 50/60 Hz AC, DC		2-sided, 40 m
TWTE651WK	220-240 V, 50/60 Hz AC, DC		2-sided, 60 m
TWTE751WK	220-240 V, 50/60 Hz AC, DC		2-sided, 60 m
TWTE851WK	220-240 V, 50/60 Hz AC, DC		1-sided, 40 m

We reserve the rights to make modifications without notice.
 Copyright © 2024 Teknoware. All rights reserved.
 Date: July 16, 2024 | Source: [teknoware.com/en/our-solutions/emergency-lighting-buildings/emergency-exit-lights/emergency-exit-light-product-families/steel-emergency-exit-light](https://www.teknoware.com/en/our-solutions/emergency-lighting-buildings/emergency-exit-lights/emergency-exit-light-product-families/steel-emergency-exit-light)



Product Code	Nominal Supply Voltage	Pictogram	Pictogram Info
TWTE951WK	220-240 V, 50/60 Hz AC, DC		1-sided, 60 m