


LINESPOT II: LOWBAY, RECESS-MOUNTED EMERGENCY LIGHTS



The Linespot II Lowbay is a compact and stylish emergency light designed especially for corridor lighting. The luminaire is recess mounted; the size of the recess mounting aperture is $\varnothing$ 75 mm.

Linespot II Lowbay's design is an unobtrusive solution for energy-efficient emergency lighting.

We reserve the rights to make modifications without notice.
Copyright © 2024 Teknoware. All rights reserved.
Date: April 24, 2024 | Source: teknoware.com/en/emergency-lighting/emergency-lights/emergency-light-product-families/linespot-ii-lowbay-recess-mounted-emergency-lights

Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland
Tel +358 3 883 020 | VAT-number FI01494751 | teknoware.com | emexit@teknoware.com



SELF-CONTAINED ESCAP EMERGENCY LIGHTS WITH SUPER CAPACITOR AND SELF-TESTING

We reserve the rights to make modifications without notice.

Copyright © 2024 Teknoware. All rights reserved.

Date: April 24, 2024 | Source: teknoware.com/en/emergency-lighting/emergency-lights/emergency-light-product-families/linespot-ii-lowbay-recess-mounted-emergency-lights



Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland
Tel +358 3 883 020 | VAT-number FI01494751 | teknoware.com | emexit@teknoware.com

Product Code	Nominal Supply Voltage	Feature	Backup (h)	Form
TWS1492WM4	220-240 V, 50/60 Hz AC	Escap, Lumi Test	1	
TWS1492WM	220-240 V, 50/60 Hz AC	Escap, Lumi Test	1	
Y1492WM	220-240 V, 50/60 Hz AC	Escap, Lumi Test	1	

SELF-CONTAINED ESCAP EMERGENCY LIGHTS WITH SUPER CAPACITOR AND WIRELESS CENTRAL MONITORING

Product Code	Nominal Supply Voltage	Feature	Backup (h)
TWS1492WA4	220-240 V, 50/60 Hz AC	Aalto Control, Escap, Lumi Test	1
TWS1492WA	220-240 V, 50/60 Hz AC	Aalto Control, Escap, Lumi Test	1
Y1492WA	220-240 V, 50/60 Hz AC	Aalto Control, Escap, Lumi Test	1

SELF-CONTAINED EMERGENCY LIGHTS WITH BATTERY AND SELF-TESTING

Product Code	Nominal Supply Voltage	Feature	Backup (h)
TWT1452WM	220-240 V, 50/60 Hz AC	Lumi Test	1
Y1452WM	220-240 V, 50/60 Hz AC	Lumi Test	1
TWT1453WM	220-240 V, 50/60 Hz AC	Lumi Test	3
Y1453WM	220-240 V, 50/60 Hz AC	Lumi Test	3

SELF-CONTAINED EMERGENCY LIGHTS WITH BATTERY AND WIRELESS CENTRAL MONITORING

Product Code	Nominal Supply Voltage	Feature	Backup (h)
TWT1452WA	220-240 V, 50/60 Hz AC	Aalto Control, Lumi Test	1
Y1452WA	220-240 V, 50/60 Hz AC	Aalto Control, Lumi Test	1
TWT1453WA	220-240 V, 50/60 Hz AC	Aalto Control, Lumi Test	3
Y1453WA	220-240 V, 50/60 Hz AC	Aalto Control, Lumi Test	3

ADDRESSABLE 230 V CENTRALLY SUPPLIED EMERGENCY LIGHTS

Product Code	Nominal Supply Voltage	Feature
TWT1451WK	220-240 V, 50/60 Hz AC, DC	Intelligent Controller, Tapsa Control
Y1451WK	220-240 V, 50/60 Hz AC, DC	Intelligent Controller, Tapsa Control

We reserve the rights to make modifications without notice.
 Copyright © 2024 Teknoware. All rights reserved.
 Date: April 24, 2024 | Source: [teknoware.com/en/emergency-lighting/emergency-lights/emergency-light-product-families/linespot-ii-lowbay-recess-mounted-emergency-lights](https://www.teknoware.com/en/emergency-lighting/emergency-lights/emergency-light-product-families/linespot-ii-lowbay-recess-mounted-emergency-lights)

Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland
 Tel +358 3 883 020 | VAT-number FI01494751 | [teknoware.com](https://www.teknoware.com) | emexit@teknoware.com



NON-ADDRESSABLE 230 V CENTRALLY SUPPLIED EMERGENCY LIGHTS

We reserve the rights to make modifications without notice.

Copyright © 2024 Teknoware. All rights reserved.

Date: April 24, 2024 | Source: teknoware.com/en/emergency-lighting/emergency-lights/emergency-light-product-families/linespot-ii-lowbay-recess-mounted-emergency-lights



Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland
Tel +358 3 883 020 | VAT-number FI01494751 | teknoware.com | emexit@teknoware.com

Product Code	Nominal Supply Voltage	Feature	Form
TWT1471W	24-230 V, 50/60 Hz AC, DC		
Y1471W	24-230 V, 50/60 Hz AC, DC		

ADDRESSABLE 24 V CENTRALLY SUPPLIED EMERGENCY LIGHTS

Product Code	Nominal Supply Voltage	Feature	Form
TWT1441WK	24 V, 50/60 Hz AC, DC	Tapsa Control	
Y1441WK	24 V, 50/60 Hz AC, DC	Tapsa Control	

We reserve the rights to make modifications without notice.

Copyright © 2024 Teknoware. All rights reserved.

Date: April 24, 2024 | Source: teknoware.com/en/emergency-lighting/emergency-lights/emergency-light-product-families/linespot-ii-lowbay-recess-mounted-emergency-lights



Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland
Tel +358 3 883 020 | VAT-number FI01494751 | teknoware.com | emexit@teknoware.com