


TKT65B CENTRAL BATTERY SYSTEMS



TKT65B series central battery system offers an effective solution to supply medium to high number of emergency and exit lights. It is suitable for medium sized buildings.

The new TKT65xxBP models are equipped with a door and their enclosure class is IP34.

Technical data:

input voltage 230 VAC

output voltage under normal conditions 230 VAC

output voltage in battery mode 216 VDC

We reserve the rights to make modifications without notice.

Copyright © 2024 Teknoware. All rights reserved.

Date: July 16, 2024 | Source: teknoware.com/en/emergency-lighting/central-battery-systems/central-battery-systems-product-families/tkt65b-central-battery-systems



Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland
Tel +358 3 883 020 | VAT-number FI01494751 | teknoware.com | emexit@teknoware.com

battery voltage of 216 V is generated by 18 pieces of 12 V batteries connected in series
 6, 12, 18 or 24 output circuits
 max 16 luminaires per circuit
 NON-ADDRESSABLE 230 V CENTRAL BATTERY SYSTEMS

Product Code	Nominal Supply Voltage	Number of Output Circuits	Max Load of Circuits (VA)
TKT6506BP	1~ N/PE 220-240 VAC, 50 Hz	6 x 250 VA / W	
TKT6506B	1~ N/PE 220-240 VAC, 50 Hz	6 x 250 VA / W	
TKT6512BP	1~ N/PE 220-240 VAC, 50 Hz	12 x 250 VA / W	
TKT6512B	1~ N/PE 220-240 VAC, 50 Hz	12 x 250 VA / W	
TKT6518BP	1~ N/PE 220-240 VAC, 50 Hz	18 x 250 VA / W	
TKT6518B	1~ N/PE 220-240 VAC, 50 Hz	18 x 250 VA / W	
TKT6524BP	1~ N/PE 220-240 VAC, 50 Hz	24 x 250 VA / W	
TKT6524B	1~ N/PE 220-240 VAC, 50 Hz	24 x 250 VA / W	
TKT6506BF	3~ N/PE 220-240/380-415 VAC, 50/60 Hz	6 x 250 VA / W	
TKT6512BF	3~ N/PE 220-240/380-415 VAC, 50/60 Hz	12 x 250 VA / W	
TKT6518BF	3~ N/PE 220-240/380-415 VAC, 50/60 Hz	18 x 250 VA / W	
TKT6524BF	3~ N/PE 220-240/380-415 VAC, 50/60 Hz	24 x 250 VA / W	