

TKT67C CENTRAL BATTERY SYSTEMS

We reserve the rights to make modifications without notice.

Copyright © 2024 Teknoware. All rights reserved.

Date: August 14, 2024 | Source: teknoware.com/en/emergency-lighting/central-battery-systems/central-battery-systems-product-families/kt67c-central-battery-systems

Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland
Tel +358 3 883 020 | VAT-number FI01494751 | teknoware.com | emexit@teknoware.com






We reserve the rights to make modifications without notice.

Copyright © 2024 Teknoware. All rights reserved.

Date: August 14, 2024 | Source: teknoware.com/en/emergency-lighting/central-battery-systems/central-battery-systems-product-families/tkt67c-central-battery-systems

Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland
Tel +358 3 883 020 | VAT-number FI01494751 | teknoware.com | emexit@teknoware.com





Central battery systems in TKT67 series give an efficient solution for a large number of luminaires. They are particularly suitable for large buildings.

TKT67C is quick to assemble as the terminals are conveniently located on the upper side of the unit and the fuses of the output circuits are at the terminals.

Technical data:

input voltage 220-240 VAC

output voltage in normal mode 220-240 VAC

output voltage in battery mode 216 VDC

battery voltage of 216 V is generated by 18 pieces of 12 V batteries connected in series

16, 24, 32, 40, 48 or 56 output circuits

8 x 350 VA, 4 x 700 VA or 2 x 1400 VA parallel connections are possible

max 32 luminaires per circuit (please note local restrictions)

ADDRESSABLE 230 V CENTRAL BATTERY SYSTEMS

Product Code	Nominal Supply Voltage	Number of Output Circuits	Max Load of Circuits (VA)
TKT6716C	3~ N/PE 220-240/380-415 VAC, 50/60 Hz	16 x 350 VA / W	
TKT6724C	3~ N/PE 220-240/380-415 VAC, 50/60 Hz	24 x 350 VA / W	
TKT6732C	3~ N/PE 220-240/380-415 VAC, 50/60 Hz	32 x 350 VA / W	
TKT6740C	3~ N/PE 220-240/380-415 VAC, 50/60 Hz	40 x 350 VA / W	
TKT6748C	3~ N/PE 220-240/380-415 VAC, 50/60 Hz	48 x 350 VA / W	
TKT6756C	3~ N/PE 220-240/380-415 VAC, 50/60 Hz	56 x 350 VA / W	

We reserve the rights to make modifications without notice.

Copyright © 2024 Teknoware. All rights reserved.

Date: August 14, 2024 | Source: [teknoware.com/en/emergency-lighting/central-battery-systems/central-battery-systems-product-families/kt67c-central-battery-systems](https://www.teknoware.com/en/emergency-lighting/central-battery-systems/central-battery-systems-product-families/kt67c-central-battery-systems)



Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland
Tel +358 3 883 020 | VAT-number FI01494751 | [teknoware.com](https://www.teknoware.com) | emexit@teknoware.com