


SOLID EXIT 2 EMERGENCY EXIT LIGHTS



The Solid Exit 2 emergency exit light is equipped with a light plate. The luminaire is designed specifically to withstand harsh conditions. It is a IP65 enclosure classed luminaire and completely dust and water proof.

Solid Exit 2 is suitable for example for industrial premises, parking halls and outdoor use.

Special attention has been paid to the design for easy installation.

SELF-CONTAINED ESCAP EMERGENCY EXIT LIGHTS WITH SUPER CAPACITOR AND SELF-TESTING

Product Code	Nominal Supply Voltage	Pictogram	Pictogram Info	Backup (h)
TWS3192WM	220-240 V, 50/60 Hz AC		2-sided, 30 m	1
Y3192WM143	220-240 V, 50/60 Hz AC		2-sided, 30 m	1
Y3192WM148	220-240 V, 50/60 Hz AC		1-sided, 30 m	1
Y3192WM147	220-240 V, 50/60 Hz AC		1-sided, 30 m	1
Y3192WM145	220-240 V, 50/60 Hz AC		2-sided, 30 m	1
Y3192WM149	220-240 V, 50/60 Hz AC		1-sided, 30 m	1
Y3192WM141	220-240 V, 50/60 Hz AC		2-sided, 30 m	1
Y3192WM142	220-240 V, 50/60 Hz AC		1-sided, 30 m	1

We reserve the rights to make modifications without notice.
Copyright © 2024 Teknoware. All rights reserved.
Date: April 25, 2024 | Source: teknoware.com/en/emergency-lighting/emergency-exit-lights/emergency-exit-light-product-families/solid-exit-2-emergency-exit-lights

SELF-CONTAINED ESCAP EMERGENCY EXIT LIGHTS WITH SUPER CAPACITOR AND WIRELESS CENTRAL MONITORING

Product Code	Nominal Supply Voltage	Pictogram	Pictogram Info	Backup (h)
TWS3192WA	220-240 V, 50/60 Hz AC		2-sided, 30 m	1
Y3192WA143	220-240 V, 50/60 Hz AC		2-sided, 30 m	1
Y3192WA148	220-240 V, 50/60 Hz AC		1-sided, 30 m	1
Y3192WA147	220-240 V, 50/60 Hz AC		1-sided, 30 m	1
Y3192WA145	220-240 V, 50/60 Hz AC		2-sided, 30 m	1
Y3192WA149	220-240 V, 50/60 Hz AC		1-sided, 30 m	1
Y3192WA141	220-240 V, 50/60 Hz AC		2-sided, 30 m	1
Y3192WA142	220-240 V, 50/60 Hz AC		1-sided, 30 m	1

SELF-CONTAINED EMERGENCY EXIT LIGHTS WITH BATTERY AND SELF-TESTING

Product Code	Nominal Supply Voltage	Pictogram	Pictogram Info	Backup (h)
TWT3153WM	220-240 V, 50/60 Hz AC		2-sided, 30 m	3

SELF-CONTAINED EMERGENCY EXIT LIGHTS WITH BATTERY AND WIRELESS CENTRAL MONITORING

Product Code	Nominal Supply Voltage	Pictogram	Pictogram Info	Backup (h)
TWT3153WA	220-240 V, 50/60 Hz AC		2-sided, 30 m	3

ADDRESSABLE 230 V CENTRALLY SUPPLIED EMERGENCY EXIT LIGHTS

Product Code	Nominal Supply Voltage	Pictogram	Pictogram Info
TWT3151WK	220-240 V, 50/60 Hz AC, DC		2-sided, 30 m
Y3151WK143	220-240 V, 50/60 Hz AC, DC		2-sided, 30 m
Y3151WK148	220-240 V, 50/60 Hz AC, DC		1-sided, 30 m
Y3151WK147	220-240 V, 50/60 Hz AC, DC		1-sided, 30 m
Y3151WK145	220-240 V, 50/60 Hz AC, DC		2-sided, 30 m
Y3151WK149	220-240 V, 50/60 Hz AC, DC		1-sided, 30 m

We reserve the rights to make modifications without notice.

Copyright © 2024 Teknoware. All rights reserved.

Date: April 25, 2024 | Source: teknoware.com/en/emergency-lighting/emergency-exit-lights/emergency-exit-light-product-families/solid-exit-2-emergency-exit-lights

Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland
Tel +358 3 883 020 | VAT-number FI01494751 | teknoware.com | emexit@teknoware.com



NON-ADDRESSABLE 230 V CENTRALLY SUPPLIED EMERGENCY EXIT LIGHTS

We reserve the rights to make modifications without notice.

Copyright © 2024 Teknoware. All rights reserved.

Date: April 25, 2024 | Source: teknoware.com/en/emergency-lighting/emergency-exit-lights/emergency-exit-light-product-families/solid-exit-2-emergency-exit-lights

Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland
Tel +358 3 883 020 | VAT-number FI01494751 | teknoware.com | emexit@teknoware.com



Product Code	Nominal Supply Voltage	Pictogram	Pictogram Info
TWT3171W	24-230 V, 50/60 Hz AC, DC		2-sided, 30 m
Y3171W143	24-230 V, 50/60 Hz AC, DC		2-sided, 30 m
Y3171W148	24-230 V, 50/60 Hz AC, DC		1-sided, 30 m
Y3171W147	24-230 V, 50/60 Hz AC, DC		1-sided, 30 m
Y3171W145	24-230 V, 50/60 Hz AC, DC		2-sided, 30 m
Y3171W149	24-230 V, 50/60 Hz AC, DC		1-sided, 30 m
Y3171W141	24-230 V, 50/60 Hz AC, DC		2-sided, 30 m
Y3171W142	24-230 V, 50/60 Hz AC, DC		1-sided, 30 m

We reserve the rights to make modifications without notice.

Copyright © 2024 Teknoware. All rights reserved.

Date: April 25, 2024 | Source: teknoware.com/en/emergency-lighting/emergency-exit-lights/emergency-exit-light-product-families/solid-exit-2-emergency-exit-lights



Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland
Tel +358 3 883 020 | VAT-number FI01494751 | teknoware.com | emexit@teknoware.com